

1.1.1 AUTOMOTIVE OILS



1.1.2 GASOLINA HD SAE 30, 40 Y 50 API-SF

This product is formulated for preventing rust and corrosion, keeping the engine clean and reducing oil consumption. We recommend this fuel to be used in automobiles, trucks, tractors, etc. This is, it can be used in all units satisfactorily covering the API SF/CC service and other specifications.

1.1.3 GASOLINA HD SAE 15W 40

SG/CD classification, lubricating oil CDII for models from 1989. This keeps the engine clean and free of residues, reduces starting friction, it can be used in old models with API-SC-CC service.

1.1.4 DIESEL SAE 10W, 20W, 30 Y 40

This product is formulated for fulfilling the high-speed diesel engines needs. In this way these engines can operate with extra weight and in adverse conditions. This is recommended for all kind of mobile equipment, diesel: General Motors, Ford, Chrysler, etc. It meets all of the API, CD/CE, C-3, ALLISON, MIL-L 2104, and MIL-L-451998, CD/CF specifications.

1.1.5 DIESEL SAE 15W 40 SAE CE

API CF/CF2, CD/CF2, CD/CD-II/T02 classification. Formulated oil for keeping a proper TBN even with high sulphur content diesel fuel. This oil is fabricated for protecting starting with low and high temperatures in equipments with extra heavy load. It is used for exhausting or turbo- loaded diesel engines.

1.1.6 LUBDECO ATF 220

This product is created by using basics with a high viscosity level and special additives. It meets General Motors (Dextron II, D-series), Ford (Mercon and M2C166-H), Dimier-Benz (West Coast), Alison C-4/C-3 fluids and Caterpillar To-2 fluids requirements.