

1.2.1 INDUSTRIAL OILS



1.2.2 LUBDECO TRANSMISION SAE 90, 140 Y 150

Oils produced with high quality basics and great viscosity grade protecting under normal temperatures from oxidation with good water separation. This product is recommended to be applied on single bearings, slides, machines, tools, low or normal load closed gears, normal temperature and light load circulating.

1.2.3 LUBDECO HIDRAULICO 150, 220, 300, 460

These oils have antirust and oxidation properties. They have an excellent viscosity level. They are recommended to be used in hydraulic systems for presses, hoists, shears, tractors and machinery off- the- road. These oils passed the test applied by Denison HF-2 Vickers, LH-06-01, LH-15-1, U.S. Steel Reg. No. 126, 127, 136, 137.

1.2.4 LUBDECO TRACTOR 303

This is a product formed by basics and a package of additives to be used in tractors and in agricultural machinery. This provides stability in corrosion, oxidation, antirust, and quick water removal. This is recommended to be used with agricultural mobile equipment as Jhon Deere, Allis Chaimers, Ford Motor Co. International Harvester, Massey Ferguson, covering the following requirements: JD, J20, J14B, A.C.H., PF 821, ACM 7201, F.M. M2C134-A, M2C541, M2C41, I.H, HY-TRANS, B6, M.F., M1127, M-1135, M-1129.