



3.1.1 LUBRICANTS FOR ALUMINUM INJECTION MACHINES

3.1.4 LUBDECO A 800

This is a synthetic, not pigmented product, for demoulding aluminum-injected pieces.

PERFORMANCE:

Excellent demoulding effect, its working temperature is exceptionally wide at 430° C it provides good results, LUBDECO A 650 provides a fine and uniform film with lubricating properties, it avoids the die erosion and produces a flat and brilliant surface.

It does not leave prejudicial debris when painting pieces. This is a not corrosive and not toxic formulation.

APPLICATION:

It is a concentrated product and for it to be used, it must be diluted with water, a 1:20 dilution and possible reaching the 1:60 dilution or more. This product has an easy dilution and it is quickly emulsified with water, through shaking. It must be applied by spreading.

We recommend not introducing contaminated containers in the product.

3.1.5 LUBDECO LUPOMATIC E

This is a graphite free product. It has excellent lubricating properties and extreme pressure. It can be used in the fabrication of pistons on aluminum injector machines.

APPLICATION:

This is for automatic systems, through pumps or by leakage.

PERFORMANCE:

Optimum performance. This due to a balanced composition of the product, a protecting film is formed in the jacket piston for avoiding erosion.

PHYSICAL PROPERTIES:

Consistency	Fluid
Metals affinity	Excellent
Density	0.88 to 0.92 g/cm ³

STORAGE CONDITIONS:

Store in a fresh place. Do not introduce contaminant products.